



INSTALLATION KIT

	<p>NO.L03818 4" Tenon with 1pc top cover, with outer hexagon stainless steelscrew set without gasket kit+spring gaskets, with screw plug set, with 1pc bracket with silicone gasket & silicone water proof end cap, Size: 4-3/4"x4-3/4"x10-15/64" Dark bronze</p>
	<p>NO.L03819 Tenon Mount Adaptor T-Type 7.5", with silicone gasket, Mounting Screws are not included, Size: 4"x7.5"xØ2-3/8", Dark bronze</p>
	<p>NO.L03820 90° Tenon Mount Adaptor 10", with silicone gasket, Mounting Screws are not included, Size: 4"x10"xØ2-3/8", Dark bronze</p>
	<p>NO.L03821 90° Tenon Mount Adaptor 16", with silicone gasket, Mounting Screws are not included, Size: 4"x16"xØ2-3/8", Dark bronze</p>

Wall mount 壁灯安装杆件力学报告

杆件都采用碳钢材料。墙壁安装板厚度为 6mm，圆杆直径为 60mm，壁厚 3mm 焊接而成。由 4 颗 M10 螺丝固定于墙壁，总长为 412mm。在下图所示的圆杆顶部向下施加 420N(43KG,也就是四个 AL300W 的重量)的力，杆件的安装板以及圆杆处会受到应力，但是未超出材料的屈服强度，位移也在合格范围内，因此合格。



